


NTBR Series Stainless Steel Optical Breadboard, 50/100/150/200/300mm



Naming rule:

NTBR 6 6 - 100 (-304) (-316)



Features:

- The standard table top surface material is SUS430 (1Cr17) high magnetic conductivity stainless steel. In addition, SUS304 weak magnetic conductivity stainless steel, SUS316 extremely weak magnetic conductivity stainless steel are also available.
- Matte black processed, low reflection working surface.
- The side material is blue PU leather, beautiful and practical, and the four corners are covered with stainless steel plate.

Specifications:

- Surface Flatness: 0.02~0.05mm/600mm×600mm
- Working surface: 4~6mmthick stainless steel
- Bottom Skin: 4~6mm thick carbon steel
- Overall thickness: 50/100/150/200/300mm
- Mounting hole grid: 25mm×25mm
- Mounting hole to borders: 37.5mm
- Mounting hole: M6
- Weight: 50mm thickness: about110kg/m²
100mm thickness: about120kg/m²
150mm thickness: about130kg/m²
200mm thickness: about140kg/m²
300mm thickness: about167kg/m²

Selection Table:

Model	Size(mm)
NTBR33-50	300×300×50
NTBR345-50	450×300×50
NTBR4545-50	450×450×50
NTBR36-50	600×300×50
NTBR456-50	600×450×50
NTBR66-100	600×600×100
NTBR459-100	900×450×100
NTBR69-100	900×600×100
NTBR99-100	900×900×100
NTBR810-100	1000×800×100
NTBR612-100	1200×600×100
NTBR812-100	1200×800×100
NTBR912-100	1200×900×100
NTBR1212-100	1200×1200×100
NTBR615-100	1500×600×100
NTBR915-100	1500×900×100
NTBR915-150	1500×900×150
NTBR915-200	1500×900×200
NTBR1015-100	1500×1000×100
NTBR1015-150	1500×1000×150
NTBR1015-200	1500×1000×200
NTBR1215-100	1500×1200×100
NTBR1215-150	1500×1200×150
NTBR1215-200	1500×1200×200
NTBR1515-100	1500×1500×100
NTBR1515-150	1500×1500×150
NTBR1515-200	1500×1500×200

Model	Size(mm)
NTBR918-100	1800×900×100
NTBR918-150	1800×900×150
NTBR918-200	1800×900×200
NTBR1018-100	1800×1000×100
NTBR1018-150	1800×1000×150
NTBR1018-200	1800×1000×200
NTBR1218-100	1800×1200×100
NTBR1218-150	1800×1200×150
NTBR1218-200	1800×1200×200
NTBR1518-100	1800×1500×100
NTBR1518-150	1800×1500×150
NTBR1518-200	1800×1500×200
NTBR1020-150	2000×1000×150
NTBR1020-200	2000×1000×200
NTBR1220-150	2000×1200×150
NTBR1220-200	2000×1200×200
NTBR1520-150	2000×1500×150
NTBR1520-200	2000×1500×200
NTBR1224-150	2400×1200×150
NTBR1224-200	2400×1200×200
NTBR1524-150	2400×1500×150
NTBR1524-200	2400×1500×200
NTBR1230-200	3000×1200×200
NTBR1230-300	3000×1200×300
NTBR1530-200	3000×1500×200
NTBR1530-300	3000×1500×300